

### DHG50135-4 High current slip ring

Slip rings of the DHG50135-4 is specially design for high current 50A~280A, High current can be customized as per actual demand.

#### Features

- ◆ Integrated structure design for easy installation
- ◆ 150A, 100A, 500, 1000A or higher current are available
- ◆ Various sizes with internal or external thread installation
- ◆ IP 51 (IP54-IP68 can be customized)
- ◆ Signals combination with high current is available

#### Typical applications

- ◆ Automatic machines
- ◆ Oil drilling
- ◆ Port machinery
- ◆ Marine
- ◆ Crane

#### Options

- ◆ Working speed
- ◆ Rated voltage
- ◆ Rated current
- ◆ No. of rings
- ◆ Connector
- ◆ Housing material
- ◆ Position of wire outlet, wire length
- ◆ Protection level (dust and water)
- ◆ Flange mounting is optional

## Specifications for DHG50135-4

Electrical Data		Mechanical Data	
No. of Rings	4rings	Inner Diameter	50mm
Rated Current	280A/ring	Outer Diameter	135mm
Rated Voltage	660VAC/240VDC	Working Speed	0-300rpm
Dielectric Strength	2500VAC@50HZ,60S	Working Temperature	-20°C~+80°C
Insulation Resistance	1000MΩ/1000VDC	Working Humidity	60% RH or higher
Electrical Noise	<0.01Ω	Structure Material	Engineering plastics
		Contact material	Precious material
		IP Rating	IP51

## Drawing for Outline Dimension

